

CLCM 2.0

Communication Life Cycle Manager 2.0





We live electronics!



Communication Lifecycle Manager 2.0

Key Features



Web-based tool



Management of all fieldbus-based data from specification to release



Development, mapping and maintenance of the communication interfaces of ECUs



Description of the entire data flow between ECUs and in the ECU itself



Simple linking with the Sontheim MDT®



ODX 2.2.0 Support

The Communication Lifecycle Manager 2.0

The CLCM 2.0 of the Sontheim Industrie Elektronik GmbH is a centralized system for managing and authoring the diagnostic and communication description of ECUs and complete vehicles. It is a client-server-based web application that allows several users to work collaboratively on the same project. There is no client installation necessary and the server can be accessed from different platforms via browser.

The CLCM 2.0 can be integrated in the existing infrastructure and development workflow. It is intended to accompany the whole development process of ECUs or vehicle:

All advantages at a glance:

- Beginning with a high-level overall vehicle structure during the requirements phase
- More refined specification of the ECUs during implementation phase
- Validation of the described network during testing phase
- Provision of generated source code, documentation and diagnostic description after the release

System Overview



Diagnostic and communication description

The diagnostic interface of the ECUs is defined in ODX 2.2.0 format. In addition, a description of the communication between ECUs within the vehicle network can be added. The described diagnostic data serve as the base data for source code and documentation generation.

The data is stored in a database server that allows management of large diagnostic projects. Existing legacy data or vendor supplied data can be imported. The database keeps a change history that allows to export and view previous (= older) states.

CLCM 2.0 is independent of the protocol and communication system which is used to describe the diagnostics and communication data. Thus, various technologies are supported, including: CAN, K-Line, Ethernet, EtherCAT, J1939, KWP2000onCAN, UDS, CANOpen, UDP, TCP/IP etc.



er by Ownership:	Filter by Hash-Tag:	Conly own Locked F	iles 📄 Only own Unlocked Files 📄 In	nclusive Subfolders Apply F	lter
the Wronal1939,SEpde	🔤 🖪 🕄 🕞	0 0 0 1	11 III @ % 🗟		Fifter by:
Wernal 1939 SE ody	FileName	Location	Hash-Tags	User Lock	Owners
- man har been	VeronaOtxGenerator.dll	Veronal 1939_SE.pdx	0		GLOBAL
	TruckAndBusOnGAN.ode-c	Veronal1939_SIE.pdx	0		GLOBAL
	SIE_Terminal_J1939.odx	Wronal1939_SE.pdx	0	DebugUser	GLOBAL
	Action_CPSS.ode-cs	Veronal 1939_SiE.pdx	0		GL084L
	SAE_/1908_11_DWCAN_CPSS.ode+	s Weronal1939_SiE.pdx	0		GL084L
	odioad	Wronal1939_SiE.pdx	0		GLOBAL
	ode-shtml.esd	Veronal1939_SIE.pdx	0		GL0844.
	ods-cc.std	Veronal1939_SIE.pdx	0		GLOBAL
	Action_OPS.ode-c	Veronal1939_SE.pdx	0		GLOBAL
	Diaglayer_IMMEControl.odx	Verona/1939_SIE.pdx	0		GLOBAL
	SAE_J1939_21_OPSS.ode-cs	Veronal 1939_SE.pdx	0		GLOBAL

Editing Views

ODX Explorer

The CLCM 2.0 features an ODX Explorer that allows the navigation through the hierarchical structure of an ODX file and provides form-based editors for the elements.

For example, this view allows users with advanced ODX knowledge to define the overall structure of an ODX file and also to make specific changes to certain elements.

The view provides usability features like reference handling, search and copy&paste.

Odx - Action_CPSS.odx-cs ComparamSubset - ComparamSubset ActionDII	🗄 Save 🛛 🛪 Cancel		FBp 👻 Search	0
irCospece: ∀ Corpora. Monartine/icon	COMPARAM			0
	ID:	SE_ACTIONDLLCOMPARAMMINMINORVERSION.ID	٩	. 8
	OID:			
	PARAM-CLASS:	COM		
	CPTYPE:	1		
	DISPLAY-LEVEL:	APPLICATION		
	SHORT NAME	MinimumMinorWersion		115
	O LONG-NAME			0
	· Whee	Minimum of Minor Version		
	O DISC			
	PHYSICAL DEFAULT	value 0		
	DATA-OBJECT-PROP	- 82F		G
	ID-REF:	SIE_ACTIONDLLCOMPARAMDOP/VERSIONUD	0	
	DOCREF:			
	DOCTVPE:			
	REVISION			

Grid View

The CLCM 2.0 features a Grid View that allows a generic and protocol specific representation of commonly used data structures, e.g.: DIAG-SERVICES, TABLES, DTCS and ENV-DATAS.

For example, this view allows an ECU developer to define multiple diagnostic services that have the same fundamental structure and only have different identifiers and payload data. The underlying complex ODX structures are hidden and displayed in a simplified way to only show the relevant information necessary to accomplish this task.

The Grid View has wide-scaled customization possibilities to incorporate company specific guidelines for the diagnostic description.

ADCORDON	•	New Y	🖉 Edit 🗙 Delete Ď Copy 🏙 P		Paste								
u.			ShortName		LongName								
,11939													
11939 0	~	۹ 🗆	AmbCondition	AmbCondition									
11939 03	~	۹ 🗆	D5_A1SCRDSI1		US,A	DS_Attertreatment 1 SCR Dosing System							
14030 3	×	۹ 🗆	DS_ActiveFaults_DM1			DS_ActiveFaults_DM1							
11939_3	~	V Q DS_AmbientConditions		10.000	DS_AmbientConditions								
11939_61	^	4 🗆	US AT TOOL			05,008	peasies 11	Ansee Unication C	acaryst				
		O New	 ✓ Ø. Edit 	× Delete	Copy	R Paste		+ Mov	e 🛧 N	fove Up	↓ Move Down		
			LongName			BytePos	iti BitPositie	e DataType	BitLengt	Default	Dop		
			Para	emeter Group	Number	0		AUInt32	24	64800			
						3		_AUInt32	16		DOP_28yte_U	INT_273_0_03215_d	eqC
					0			_PLUTID2	10		DOP_Zaya_0		ig.
	- C.												
	č	a H	DS ATTIMS	Ki l		DS Aftertreatment 1 Gas Parameters			5				
	^	Q 🗆	DS_AT1S_After	Treatment_1Se	tmnt_1Servc		DS_AT1S Aftertreatment 1 Service						
		O New	 ✓ & Edit 	× Delete	🔊 Сору	R Paste		+ Mov	e 🛧 h	love Up	↓ Move Down		
			Type	ShortName			Long	Name			BytePositi BitPos	itice DataType	BitLength
			CodedConst		PGN			Parameter Gr	oup Numb	er .	0	AUHA32	24
			Value		OPF_Soot_Load	Percent		DPF_Soot_L	sad_Percer	d	3	_AUInt32	8
			Value	DPF_Ash_Load_Pe		Percent DPF_Ash_Load_Per		ad Percen		4	_AUint32	8	
			Value	Time	_sinceLastAct_R	egeneration		Time_sinceLastA		ation	5	AUnt32	32
	24	0	DS CAN Marrie	ine .		DS CAN Message							
							DS CM1 Receive Message						

Vehicle View

The CLCM 2.0 features a Vehicle View for the high-level management of different vehicle types of a company. For each vehicle model the bus and the connected ECUs can be represented to give an overview of communication within the vehicle network.

It allows the assignment of software packages and the released software version for the ECUs.



Test View

The CLCM 2.0 features a Test View that allows to verify the defined diagnostic services against the actual ECU or simulation. Services are configured and executed using MDT[®] 2.0. It is a D-PDU API based runtime system. The connection with the ECU is realized either with:

- A locally connected VCI via USB (e.g. SiE MT-API) or
- An ethernet based VCI via LAN/WLAN (e.g. using J2534)

Code Generator

The CLCM 2.0 features a customizable code generation mechanism that can be used to create source code and documentation that is based on the diagnostic data. The output is fully customizable and can be used by different platforms and programming languages. This allows the integration in existing software modules and libraries.

Possible uses cases are:

- Source code for ECU software, diagnostic application and testing environments
- Documentation for development, production and service department

The code generation mechanism can be integrated in the customer specific build infrastructure.

Extension API

The CLCM 2.0 features an Extension API that allows to modify the default views and also allows the creation of new customer specific views. Extensions are written in a .NET programming language (e.g. C#) and have access to the complete diagnostic data of the projects.

User Management

- Access to data and files can be restricted for specific user groups and individual users
- Features can be enabled/disabled for specific user groups and individual users
- Supports authentication via Active Directory

Technical Data



Windows Server 2016; IIS 10.0; SQL Server 2016; CPU: 4 Cores; RAM: 6 GB; Storage: 75 GB

Client Requirements (Minimum)

Web Browser (Chrome, Firefox, Edge)

<code-block><code-block><section-header><code-block></code></code></code>

Order information

V940830100	CLC Manager 2.0
C940830100	CLC Manager 2.0 Software Maintenance





Mobile Automation



Industrial Automation



Diagnostics



Connectivity

We are looking forward to your enquiry!

Sontheim Electronic Systems L.P.

201 West 2nd Street 52801 Davenport, USA Phone: +1 563 888 1471 Email: info@sontheim-esys.com

Sontheim Industrie Elektronik GmbH

Georg-Krug-Straße 2 D-87437 Kempten Phone: +49 (0) 831 575900-0 Fax: +49 (0) 831 575900-72 Email: info@s-i-e.de

www.sontheim-esys.com